

LUBIE**POLSTEAM**

NAME:	LUBIE	IMO NUMBER:	9441984
TYPE:	HANDYSIZE SINGLE DECK, DOUBLE SKINNED, OPEN HATCH, SELF-TRIMMING BULK CARRIER		
FLAG:	BAHAMAS FLAG	BUILT:	2011 / MINGDE SHIPYARD, NANTONG
CLASS:	DNV	CREW NATIONALITY:	EU
INTERNATIONAL GRT:	20603	INTERNATIONAL NRT:	9517

LOA [M]:	189,595
BEAM [M]:	23,607
DEPTH MOULDED [M]:	14,603

	SUMMER SALT WATER	WINTER SALT WATER	TROPIC SALT WATER
DWT [MTS]:	30210	29310	31111
DRAFT [M]	10,222	10,009	10,435
TPC at SUMMER DRAFT:	42,3 T/CM		

SPEED and CONSUMPTION: SEA	SPEED [KTS]:	VLSFO [MTS]:
LADEN	13,0	25,0
BALLAST	13,5	24,0

ECO SPEED and CONSUMPTION: SEA	SPEED [KTS]:	VLSFO [MTS]:
LADEN	11,5	21,0
BALLAST	12,0	20,0

CONSUMPTION: PORT	VLSFO [MTS]:	CONSUMPTION: EU PORT	MGO LS [MTS]:
IDLE	3,0		3,0
2 CRANES WORKING	4,0		4,0
3 CRANES WORKING	5,0		5,0
BUNKER QUALITY/SPECS:	GRADES AS PER ISO 8217: 2010 VLSFO 380 CST RMG 380 MGO LS DMA		

HOLDS/HATCHES:	6/6
GEAR:	3 X 30 MT (WITH GRABS 24 MT), GRAB: 3 x max7,5m3 (17,25mt) / min5,0m3 (15mt) (Bulk material grain size: 1,0 - max. 50 mm)
CO ₂ FITTED:	YES
BOW THRUSTER	YES (700kW– 951HP)
STRENGTHENED FOR HEAVY CARGOES:	YES
AUSTRALIAN HOLD LADDERS:	YES
VENTILATION:	NATURAL

CARGO CAPACITIES:

HOLD NUMBER:	GRAIN [CBM]:	GRAIN [CUBF]:
1	5009	176891,2
2	7104	250875,4
3	6239	220328,2
4	6318	223118,1
5	7117	251334,5
6	5665	200057,6
TOTAL	37452	1322605

HOLD NUMBER:	DIMENSIONS OF HOLDS - LxBxD [M]:	DIMENSIONS OF HATCHES - LxBxD [M]:
1	20,12 x 12,57(FORE)/18,18(AFT) x 14,70	12,80 x 12,80 x 1,80
2	26,52 x 21,20 x 14,70	19,20 x 17,80 x 1,80
3	22,40 x 21,20 x 14,70	19,20 x 17,80 x 1,80
4	21,52 x 21,20 x 14,70	19,20 x 17,80 x 1,80
5	26,52 x 21,20 x 14,70	19,20 x 17,80 x 1,80
6	20,80 x 18,20(FORE)/7,50(AFT) x 14,70	16,80 x 17,80 x 1,80

This description is given without guarantee (WOG),